EMC Test Report

Product Type	:	ICP DAS with Converter
Applicant	:	ICP DAS CO., LTD.
Address	:	No. 111, Kuangfu N. Rd., Hukon Shiang, Hsinchu, Taiwan 303, R.O.C
Trade Name	:	ICP DAS
Model Number	:	VP- 4131
Test Specification	:	EN 55022: 2010 +AC:2011 / Class A EN 55024: 2010 EN 61000-3-2: 2006 +A1:2009 + A2: 2009 / Class A EN 61000-3-3: 2008
Receive Date	:	May 22, 2013
Test Period	:	May 28 ~ 30, 2013
Issue Date	:	Jul. 12, 2013

Issue by

A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade City,
Taoyuan County 334, Taiwan R.O.C.
Tel：+886-3-2710188 / Fax：+886-3-2710190

Taiwan Accreditation Foundation accreditation number: 1330

Note: *This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. This document may be altered or revised by A Test Lab Techno Corp. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, or any government agencies. The test results in the report only apply to the tested sample.*

Verification of Compliance

Issued Date: 2013/07/12

Product Type	:	ICP DAS with Converter
Applicant	:	ICP DAS CO., LTD.
Address	:	No. 111, Kuangfu N. Rd., Hukon Shiang, Hsinchu, Taiwan 303, R.O.C
Trade Name	:	ICP DAS
Model Number	:	VP- 4131
EUT Rated Voltage	:	AC 100-250V, 50-60Hz, 2.0A
Test Voltage	:	230 Vac / 50 Hz
Applicable Standard	:	EN 55022:2010 +AC:2011 / Class A EN 55024:2010 EN 61000-3-2:2006+A1:2009+A2:2009 / Class A EN 61000-3-3:2008
Test Result	:	Complied
Performing Lab.	:	A Test Lab Techno Corp. No. 140-1, Changan Street, Bade City, Taoyuan County 334, Taiwan R.O.C. Tel：+886-3-2710188 / Fax：+886-3-2710190 Taiwan Accreditation Foundation accreditation number: 1330 http://www.atl-lab.com.tw/e-index.htm

The above equipment has been tested by A Test Lab Techno Corp., and found compliance with the requirements set forth in the Electromagnetic Compatibility Directive 2004/108/EC and technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved By	:		Reviewed By	:	
(Manager)		(Murphy Wang)	(Testing Engineer)		(Frank Lin)

Feature of Equipment under Test：

The model listed below is series model to VP- 4131.

Main	Software	Diversity	Mode 1
LC-101	---	1-channel AC Digital Input and 1-channel Relay Output Lighting Control Module	V
NS-205AG	---	5-Port 10/100 Mbps Ethernet with daul power input	V
USB-2019	---	8-channel Universal Analog Input Module with High Voltage Protection (RoHS), include CN-1824	V
I-7188XA	---	Embedded controller with four communication ports, 512K Flash, 512K SRAM, MiniOS7, 3000V isolated RS-485(RoHS)	
I-7188XAD	---	Embedded Controller with four communication port, 5 digits seven segment display, developing tool kit, with 512K Flash, 512K SRAM, Battery backup, MiniOS7, 3000V Isolated RS-485 (RoHS)	V
I-7188XB	---	Embedded controller with two communication ports, developing tool kit, 512K Flash, 512K SRAM, MiniOS7 (RoHS)	
I-7188XBD	---	Embedded Controller with two communication port, 5 digits seven segment display, developing tool kit, 512K Flash, 512K SRAM, MiniOS7 (RoHS)	V
I-7188XG	---	ISaGRAF Palm-Size Programmable Automation Controller (RoHS)	
I-7188XGD	---	ISaGRAF Palm-Size PAC with 5-digit 7-segment display (RoHS)	V
I-7521	---	Embedded communication controller with one RS-485 and one RS-232	
I-7521D	---	I-7521 + LED display	V
I-7016P	---	One-channel Strain Gauge Input Module (6 wires)	
I-7016PD	---	One-channel Strain Gauge Input Module with LED Display (6 wires)	V
I-7022	---	2-channel 12-bit Analog Output Module (channel to channel isolation) (RoHS)	V
I-7522A	---	Embedded communication controller with one RS-485, one RS-422 and one RS-232	
I-7522AD	---	I-7522A with seven segment display(RoHS)	V
I-7524	---	Embedded communication controller with one RS-485 and four RS-232	
I-7524D	---	I-7524 + LED display	V
I-7527	---	Embedded communication controller with one RS-485 and seven RS-232	
I-7527D	---	I-7527 + LED display	V
tET-A4	---	Tiny Ethernet module with 4-ch DO (PNP, Source)	V
tET-C4	---	Tiny Ethernet module with 4-ch DO (NPN, Sink)	V
I-87088W	---	8-Channel PWM Output and 8-Channel High Speed Counter Module (Gray Cover) (RoHS)	V
CAN-8823	---	CAN-8823 CPU Board	V
CAN-2015C	---	CANopen module of 8- channel RTD Input	V
M-7068	---	4-channel Form A Signal Relay Output and 4-channel Form C Signal Relay Output Module (Gray Cover) (RoHS)	
M-7068D	---	M-7068 with LED Display (RoHS)	V

Main	Software	Diversity	Mode 1
M-7069	---	4-channel Form A Power Relay Output and 4-channel Form C Power Relay Output Module (Gray Cover) (RoHS)	
M-7069D	---	M-7069 with LED Display (RoHS)	V
PDS-220FT	---	Programmable Device Server with 1 RS-232, 1 RS-422/485 and 1 Multi-mode ST Fiber Ports (RoHS)	
PDS-220FC	---	Programmable Device Server with 1 RS-232, 1 RS-422/485 and 1 Multi-mode SC Fiber Ports (RoHS)	
PDS-220FCS	---	Programmable Device Server with 1 RS-232, 1 RS-422/485 and 1 Single-mode SC Fiber Ports (RoHS)	V
PDS-220FCS-60	---	Programmable Device Server with 1 RS-232, 1 RS-422/485, and 1 Single-mode SC Fiber Ports (RoHS)	
TPD-280U	---	2.8 Touch HMI device with RS-485, USB, RTC (RoHS)	V
TPD-283U	---	2.8 Touch HMI device with RS-485, USB, RTC, Ethernet (RoHS)	V
VPD-132	---	3.5” Touch HMI device with RS-232/RS-485, USB, RTC, Rubber Keypad, support XV-board (RoHS)	V
VPD-132N	---	3.5” Touch HMI device with RS-232/RS-485, USB, RTC,support XV-board (RoHS)	
VPD-133	---	3.5” Touch HMI device with Ethernet, RS-232/RS-485, USB, RTC, Rubber Keypad, support XV-board (RoHS)	V
VPD-133N	---	3.5” Touch HMI device with Ethernet, RS-232/RS-485, USB, RTC, support XV-board (RoHS)	
tM-DA1P1R1	---	1-channel Analog Output, 1-channel Digital Input and 1-channel Relay Output Module	V
GST-63-M	---	Seismic Switch with Metal casing	V
VP-4131	---	Standard ViewPAC with 10.4” LCD and 3 I/O slots (Multilanguage Version of OS) (RoHS)	V
VP-4137	---	ISaGRAF based ViewPAC with 10.4" Touch LCD and 3 I/O slots (OS: Multilanguage) (RoHS)	
VP-4139	---	InduSoft Based ViewPAC with 10.4" Touch LCD and 3 I/O slots (OS: Multilanguage) (RoHS)	
DN-100	---	I/O Connector Block with DIN-Rail Mounting and 100-Pin SCSI II Connector	V
WTC-01	---	Terminal board	V
DB-24PD	---	24-channel Opto-isolated Input Board (RoHS)	V
DB-24P	---	24-channel OPTO-22 compatible Opto-isolated Input Board (RoHS)	
DB-24P/DIN	---	DB-24P with DIN-Rail Mounting (RoHS)	
DB-24PD/DIN	---	DB-24PD with DIN-Rail Mounting (RoHS)	
CN-1824	---	D-SUB25 to terminal block 16 Pin daughter board	V

Devices Description					
Product		Manufacturer	Model Number	Serial Number	Power Cord
(1)	LCD Monitor	DELL	U2711	CN0H530T7426105K043L	Non-Shielded, 1.8m
(2)	Keyboard	HP	KU-0316	BC3870DVBVI1PJ	Power by PC
(3)	Mouse	Logitech	M-UAG96B	PID-LZ815AA	Power by PC
(4)	PC	SYNNEX	MBD-K6XV3	N/A	Non-Shielded, 1.8m
※ PC Keypart information					
Main		Software	Diversity		
(4)-1	PIO-D144U	---	Universal PCI, 144-channel DIO board 5V/TTL (RoHS)		
(4)-2	PIO-D144LU	---	Universal PCI, 144-channel DIO board 5 V/COMS (RoHS)		
(4)-3	PIO-D96SU	---	Universal PCI 96-ch OPTO-22 DIO Board		
(4)-4	WDT-01	---	Intelligent Watchdog Timer card without terminal board,cable,buzzer relay,LED,temperature sensor Include :CA-0205(2-pin Black & Red Cable 0.5m); CA-2520(25-pin D-sub Cable 2.0m)		
(4)-5	WDT-02	---	Intelligent Watchdog Timer card with terminal Board and 1 meter cable Include :CA-0205(2-pin Black & Red Cable 0.5m); CA-2520(25-pin D-sub Cable 2.0m)		

Support Unit					
Product		Manufacturer	Model Number	Serial Number	Power Cord
1.	Industrial Power Supply	ICP DAS	DP-1200	N/A	Power by Host System